

Model 328x Settings

Fill in any or all fields to have your controller pre-programmed

Wifi Settings (Model 328w Only)

Access Point

Password

Security

SMTP Server Settings

Request free SMTP account for mail relay

SMTP Port

SMTP Server Name

Sender Name

Server User Name

Server Password

Notification Settings

Email Subject

Email Address 1

Email Address 2

SMS Address

Internet Settings

NTP Server 1

NTP Server 2

DNS Server 1

DNS Server 2

Listening Port Allow Incoming Connections

Remote Monitor

Server Port Send Notifications to Remote Server

Server Address

Server User Name

Server Password

Model 328x Settings cont.

Alarms

- Enable Power Failure Alarm
- Enable Power Restored Notification
- Enable Exercise Failed Alarm
- Enable Exercise Passed Notification
- Enable Maintenance Reminders

Power Failure Delay (min)

Exercise Failed Delay (hours)

Minimum Exercise Time (min)

Maintenance Hours

Maintenance Months

Alarm Bypass Delay (seconds)

Analog Input 1

H L

Analog Input 2

H L

Digital Input 1

Digital Input 2

Digital Input 3

Digital Input 4

System Settings

Location ID

Minimum Generator Voltage

Minimum Utility Voltage

Set Run Hours

- Enable Remote Start on Relay 1

Customer

Company Name

Office Use Only

Device MEID: